



呼び径①×②×③		OD1	OD2	S10S				C	M	許容差					
A	B			ID1	T1	ID2	T2			OD1	OD2	ID1	ID2	T1・2	C・M
20x20x15	$3/4 \times 3/4 \times 1/2$	27.2	21.7	23.0	2.1	17.5	2.1	28.6	28.6	+1.6 -0.8	+1.6 -0.8	± 0.8	± 0.8	+規定 しない -12.5%	± 1.6
25x25x20	$1 \times 1 \times 3/4$	34.0	27.2	28.4	2.8	23.0	2.1	38.1	38.1						
25x25x15	$1 \times 1 \times 1/2$	34.0	21.7	28.4	2.8	17.5	2.1	38.1	38.1						
32x32x25	$1 1/4 \times 1 1/4 \times 1$	42.7	34.0	37.1	2.8	28.4	2.8	47.6	47.6						
32x32x20	$1 1/4 \times 1 1/4 \times 3/4$	42.7	27.2	37.1	2.8	23.0	2.1	47.6	47.6						
32x32x15	$1 1/4 \times 1 1/4 \times 1/2$	42.7	21.7	37.1	2.8	17.5	2.1	47.6	47.6						
40x40x32	$1 1/2 \times 1 1/2 \times 1 1/4$	48.6	42.7	43.0	2.8	37.1	2.8	57.2	57.2						
40x40x25	$1 1/2 \times 1 1/2 \times 1$	48.6	34.0	43.0	2.8	28.4	2.8	57.2	57.2						
40x40x20	$1 1/2 \times 1 1/2 \times 3/4$	48.6	27.2	43.0	2.8	23.0	2.1	57.2	57.2						
40x40x15	$1 1/2 \times 1 1/2 \times 1/2$	48.6	21.7	43.0	2.8	17.5	2.1	57.2	57.2						
50x50x40	$2 \times 2 \times 1 1/2$	60.5	48.6	54.9	2.8	43.0	2.8	63.5	60.3	+1.6 -0.8	+1.6 -0.8	± 0.8	± 0.8	+規定 しない -12.5%	± 1.6
50x50x32	$2 \times 2 \times 1 1/4$	60.5	42.7	54.9	2.8	37.1	2.8	63.5	57.2						
50x50x25	$2 \times 2 \times 1$	60.5	34.0	54.9	2.8	28.4	2.8	63.5	50.8						
50x50x20	$2 \times 2 \times 3/4$	60.5	27.2	54.9	2.8	23.0	2.1	63.5	44.5						
50x50x15	$2 \times 2 \times 1/2$	60.5	21.7	54.9	2.8	17.5	2.1	63.5	44.5						
65x65x50	$2 1/2 \times 2 1/2 \times 2$	76.3	60.5	70.3	3.0	54.9	2.8	76.2	69.9						
65x65x40	$2 1/2 \times 2 1/2 \times 1 1/2$	76.3	48.6	70.3	3.0	43.0	2.8	76.2	66.7						
65x65x32	$2 1/2 \times 2 1/2 \times 1 1/4$	76.3	42.7	70.3	3.0	37.1	2.8	76.2	63.5						
65x65x25	$2 1/2 \times 2 1/2 \times 1$	76.3	34.0	70.3	3.0	28.4	2.8	76.2	57.2						
80x80x65	$3 \times 3 \times 2 1/2$	89.1	76.3	83.1	3.0	70.3	3.0	85.7	82.6						
80x80x50	$3 \times 3 \times 2$	89.1	60.5	83.1	3.0	54.9	2.8	85.7	76.2						
80x80x40	$3 \times 3 \times 1 1/2$	89.1	48.6	83.1	3.0	43.0	2.8	85.7	73.0						
80x80x32	$3 \times 3 \times 1 1/4$	89.1	42.7	83.1	3.0	37.1	2.8	85.7	69.9						
80x80x25	$3 \times 3 \times 1$	89.1	34.0	83.1	3.0	28.4	2.8	85.7	65.7						

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 304W	名称 径違いチーズ TR(S10S)	図面番号 17235
検図 芦田	尺度 フリー		
製図 滝川	日付 2017/7/21	inoç イノック株式会社	