



呼び径①×②×③		S40								許容差					
A	B	OD1	OD2	ID1	T1	ID2	T2	C	M	OD1	OD2	ID1	ID2	T1・2	C・M
20X20X15	$3/4 \times 3/4 \times 1/2$	27.2	21.7	21.4	2.9	16.1	2.8	28.6	28.6	+1.6 -0.8	+1.6 -0.8	±0.8	±0.8	+規定 しない -12.5%	±1.6
25X25X20	$1 \times 1 \times 3/4$	34.0	27.2	27.2	3.4	21.4	2.9	38.1	38.1						
25X25X15	$1 \times 1 \times 1/2$	34.0	21.7	27.2	3.4	16.1	2.8	38.1	38.1						
32X32X25	$1\ 1/4 \times 1\ 1/4 \times 1$	42.7	34.0	35.5	3.6	27.2	3.4	47.6	47.6						
32X32X20	$1\ 1/4 \times 1\ 1/4 \times 3/4$	42.7	27.2	35.5	3.6	21.4	2.9	47.6	47.6						
32X32X15	$1\ 1/4 \times 1\ 1/4 \times 1/2$	42.7	21.7	35.5	3.6	16.1	2.8	47.6	47.6						
40X40X32	$1\ 1/2 \times 1\ 1/2 \times 1\ 1/4$	48.6	42.7	41.2	3.7	35.5	3.6	57.2	57.2						
40X40X25	$1\ 1/2 \times 1\ 1/2 \times 1$	48.6	34.0	41.2	3.7	27.2	3.4	57.2	57.2						
40X40X20	$1\ 1/2 \times 1\ 1/2 \times 3/4$	48.6	27.2	41.2	3.7	21.4	2.9	57.2	57.2						
50X50X40	$2 \times 2 \times 1\ 1/2$	60.5	48.6	52.7	3.9	41.2	3.7	63.5	60.3						
50X50X32	$2 \times 2 \times 1\ 1/4$	60.5	42.7	52.7	3.9	35.5	3.6	63.5	57.2						
50X50X25	$2 \times 2 \times 1$	60.5	34.0	52.7	3.9	27.2	3.4	63.5	50.8						
65X65X50	$2\ 1/2 \times 2\ 1/2 \times 2$	76.3	60.5	65.9	5.2	52.7	3.9	76.2	69.9						
65X65X40	$2\ 1/2 \times 2\ 1/2 \times 1\ 1/2$	76.3	48.6	65.9	5.2	41.2	3.7	76.2	66.7						
80X80X65	$3 \times 3 \times 2\ 1/2$	89.1	76.3	78.1	5.5	65.9	5.2	85.7	82.6						
80X80X50	$3 \times 3 \times 2$	89.1	60.5	78.1	5.5	52.7	3.9	85.7	76.2						
80X80X40	$3 \times 3 \times 1\ 1/2$	89.1	48.6	78.1	5.5	41.2	3.7	85.7	73.0						

※ ベベルエンドの形状、寸法は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 304W	名称 径違いチーズ	図面番号 17239
検図 芦田	尺度 フリー	TR(S40)	
製図 滝川	日付 2017/7/21	inoc イノック株式会社	