



呼び径①×②		OD1	OD2	S10S				H	許容差					
A	B			ID1	T1	ID2	T2		OD1	OD2	ID1	ID2	T1・T2	H
350×300	14×12	355.6	318.5	345.6	5.0	309.5	4.5	330.2	+4.0 -3.2	+4.0	±3.2	規定 しない -12.5%	±2.4	
350×250	14×10	355.6	267.4	345.6	5.0	259.4	4.0	330.2		-3.2				
350×200	14×8	355.6	216.3	345.6	5.0	208.3	4.0	330.2		+2.4 -1.6				±1.6
400×350	16×14	406.4	355.6	396.4	5.0	345.6	5.0	355.6		+4.0 -3.2	±3.2			±3.2
400×300	16×12	406.4	318.5	396.4	5.0	309.5	4.5	355.6						
400×250	16×10	406.4	267.4	396.4	5.0	259.4	4.0	355.6						
450×400	18×16	457.2	406.4	447.2	5.0	396.4	5.0	381.0						
450×350	18×14	457.2	355.6	447.2	5.0	345.6	5.0	381.0		-3.2				
450×300	18×12	457.2	318.5	447.2	5.0	309.5	4.5	381.0		+6.4 -4.8	±4.8			±3.2
500×450	20×18	508.0	457.2	497.0	5.5	447.2	5.0	508.0						
500×400	20×16	508.0	406.4	497.0	5.5	396.4	5.0	508.0	-3.2					
550×500	22×20	558.8	508.0	547.8	5.5	497.0	5.5	508.0	+6.4 -4.8			±4.8		
550×450	22×18	558.8	457.2	547.8	5.5	447.2	5.0	508.0	+4.0			±3.2		
550×400	22×16	558.8	406.4	547.8	5.5	396.4	5.0	508.0	-3.2					
600×500	24×20	609.6	508.0	596.6	6.5	497.0	5.5	508.0	+6.4 -4.8			±4.8		
600×450	24×18	609.6	457.2	596.6	6.5	447.2	5.0	508.0	+4.0			±3.2		
600×400	24×16	609.6	406.4	596.6	6.5	396.4	5.0	508.0	-3.2					

※ ベベルエンドの形状、寸法は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による
 ※ 管継手の直角度の許容値は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 304W	名称 同心レジューサー RC(S10S)	図面番号
検図 芦田	尺度 フリー		17244
製図 滝川	日付 2017/7/21	inoć イノック株式会社	