



呼び径 (A)	フランジ各部の寸法								寸法許容差					
	内径	外径	面取り	厚さ	中心円の径	ボルト穴		隣接穴のピッチ	d	D	t	C	P	
	d	D	E	t	C	n	h	P						
15	23.4	95	C3	12	70	4	15	49.50	+1.0 0	±1.5	+1.5 0	±0.8	±0.8	
20	28.9	100	C3	14	75	4	15	53.03						
25	35.6	125	C3	14	90	4	19	63.64						
32	44.3	135	C4	16	100	4	19	70.71						
40	50.4	140	C4	16	105	4	19	74.25						
50	62.7	155	C4	16	120	4	19	84.85						
65	78.7	175	C5	18	140	4	19	98.99						
80	91.6	185	C5	18	150	8	19	57.40						
100	116.9	210	C5	18	175	8	19	66.97						
125	143.0	250	C6	20	210	8	23	80.36						
150	168.4	280	C6	22	240	8	23	91.84						
200	219.5	330	C6	22	290	12	23	75.05						+2.0 0

承認 滝川	材質 SUSF304	名称 呼び圧力10Kフランジ 遊合フランジ FFC	図面番号 19523
検図 今西	尺度 フリー		
製図 芦田	日付 2019/11/19	inoç イノック株式会社	