



呼び径 (A)	フランジ各部の寸法									寸法許容差				
	差込み 穴の径 d	外径 D	厚さ t	中心円 の径 C	ボルト穴		隣接穴 のピッチ P	ガスケット座		d	D	t	C	P
					数 n	径 h		g	f					
80	90.0	211	18	168	4	19	118.79	125	2	+0.5 0	±1	+1.5 0	±0.5	±0.5
100	115.4	238	18	195	4	19	137.89	152	2	+1 0				
125	141.2	263	20	220	6	19	110.00	177	2					
150	166.6	290	22	247	6	19	123.50	204	2		±1.5	+2 0	±0.6	±0.5
200	218.0	342	22	299	8	19	114.42	256	2					
250	269.5	410	24	360	8	23	137.76	308	2					
300	321.0	464	24	414	10	23	127.93	362	3	+1.5 0	±2	±0.8	±0.8	
350	358.1	530	26	472	10	25	145.86	414	3					
400	409.0	582	26	524	12	25	135.62	466	3					
450	460.0	652	28	585	12	27	151.41	518	3	+1.5 0	±2	±0.8	±0.8	
500	511.0	706	28	639	12	27	165.39	572	3					
600	613.0	810	30	743	16	27	144.95	676	3					+2 0

承認 滝川	材質 SUSF304	名称 F12水輸送管フランジ 平面座差込み溶接フランジ WRF	図面番号 23103
検図 今西	尺度 フリー		
製図 滝川	日付 2023/03/13	 イノック株式会社	