



| 呼び径 $\phi \times \textcircled{\text{B}}$ | | $\phi D1$ | $\phi D2$ | S10S | | | | H | 許容差 | | | | | | |
|--|-------|-----------|-----------|-------|-----|-------|-----|-------|--------------|--------------|------|-----------|-----------|------|------|
| A | B | | | ID1 | T1 | ID2 | T2 | | $\phi D1$ | $\phi D2$ | ID1 | ID2 | T1・2 | H | |
| 100x80 | 4x3 | 114.3 | 89.1 | 108.3 | 3.0 | 83.1 | 3.0 | 101.6 | ±1.6 | ±1.6 | ±1.6 | ±1.6 | 規定 しない | ±1.6 | |
| 100x65 | 4x2½ | 114.3 | 76.3 | 108.3 | 3.0 | 70.3 | 3.0 | 101.6 | | +1.6 | | | | | ±0.8 |
| 100x50 | 4x2 | 114.3 | 60.5 | 108.3 | 3.0 | 54.9 | 2.8 | 101.6 | | -0.8 | | | | | ±0.8 |
| 125x100 | 5x4 | 139.8 | 114.3 | 133.0 | 3.4 | 108.3 | 3.0 | 127.0 | ±1.6 | ±1.6 | ±1.6 | 規定 しない | ±1.6 | | |
| 125x80 | 5x3 | 139.8 | 89.1 | 133.0 | 3.4 | 83.1 | 3.0 | 127.0 | | ±1.6 | | | | ±1.6 | |
| 125x65 | 5x2½ | 139.8 | 76.3 | 133.0 | 3.4 | 70.3 | 3.0 | 127.0 | | +1.6 -0.8 | | | | ±0.8 | |
| 150x125 | 6x5 | 165.2 | 139.8 | 158.4 | 3.4 | 133.0 | 3.4 | 139.7 | +2.4 -1.6 | +2.4 -1.6 | ±1.6 | 規定 しない | ±1.6 | | |
| 150x100 | 6x4 | 165.2 | 114.3 | 158.4 | 3.4 | 108.3 | 3.0 | 139.7 | | ±1.6 | | | | ±1.6 | |
| 150x80 | 6x3 | 165.2 | 89.1 | 158.4 | 3.4 | 83.1 | 3.0 | 139.7 | | ±1.6 | | | | ±1.6 | |
| 200x150 | 8x6 | 216.3 | 165.2 | 208.3 | 4.0 | 158.4 | 3.4 | 152.4 | +2.4 -1.6 | +2.4 -1.6 | ±1.6 | 規定 しない | ±1.6 | | |
| 200x125 | 8x5 | 216.3 | 139.8 | 208.3 | 4.0 | 133.0 | 3.4 | 152.4 | | ±1.6 | | | | ±1.6 | |
| 200x100 | 8x4 | 216.3 | 114.3 | 208.3 | 4.0 | 108.3 | 3.0 | 152.4 | | ±1.6 | | | | ±1.6 | |
| 250x200 | 10x8 | 267.4 | 216.3 | 259.4 | 4.0 | 208.3 | 4.0 | 177.8 | +4.0 -3.2 | +2.4 -1.6 | ±3.2 | 規定 しない | ±2.4 | | |
| 250x150 | 10x6 | 267.4 | 165.2 | 259.4 | 4.0 | 158.4 | 3.4 | 177.8 | | ±3.2 | | | | ±3.2 | |
| 250x125 | 10x5 | 267.4 | 139.8 | 259.4 | 4.0 | 133.0 | 3.4 | 177.8 | | ±3.2 | | | | ±3.2 | |
| 300x250 | 12x10 | 318.5 | 267.4 | 309.5 | 4.5 | 259.4 | 4.0 | 203.2 | +2.4 -1.6 | +4.0 -3.2 | ±1.6 | 規定 しない | ±2.4 | | |
| 300x200 | 12x8 | 318.5 | 216.3 | 309.5 | 4.5 | 208.3 | 4.0 | 203.2 | | ±1.6 | | | | ±1.6 | |
| 300x150 | 12x6 | 318.5 | 165.2 | 309.5 | 4.5 | 158.4 | 3.4 | 203.2 | | ±1.6 | | | | ±1.6 | |

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による
 ※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

| | | | |
|----------|-----------------|----------------|---------------|
| 承認 滝川 | 材質 SUS 316LW | 名称 偏心レジューサー | 図面番号 17284 |
| 検図 芦田 | 尺度 フリー | RE(S10S) | |
| 製図 滝川 | 日付 2017/8/08 | イノック株式会社 | |