



呼び径①×②×③		OD1	OD2	S10S				C	M	許容差					
A	B			ID1	T1	ID2	T2			OD1	OD2	ID1	ID2	T1・T2	C・M
20X20X15	3/4X3/4X1/2	27.2	21.7	23.0	2.1	17.5	2.1	28.6	28.6	+1.6 -0.8	+1.6 -0.8	±0.8	±0.8	+規定 しない -12.5%	±1.6
25X25X20	1X1X3/4	34.0	27.2	28.4	2.8	23.0	2.1	38.1	38.1						
25X25X15	1X1X1/2	34.0	21.7	28.4	2.8	17.5	2.1	38.1	38.1						
32X32X25	1 1/4X1 1/4X1	42.7	34.0	37.1	2.8	28.4	2.8	47.6	47.6						
32X32X20	1 1/4X1 1/4X3/4	42.7	27.2	37.1	2.8	23.0	2.1	47.6	47.6						
32X32X15	1 1/4X1 1/4X1/2	42.7	21.7	37.1	2.8	17.5	2.1	47.6	47.6						
40X40X32	1 1/2X1 1/2X1 1/4	48.6	42.7	43.0	2.8	37.1	2.8	57.2	57.2						
40X40X25	1 1/2X1 1/2X1	48.6	34.0	43.0	2.8	28.4	2.8	57.2	57.2						
40X40X20	1 1/2X1 1/2X3/4	48.6	27.2	43.0	2.8	23.0	2.1	57.2	57.2						
50X50X40	2X2X1 1/2	60.5	48.6	54.9	2.8	43.0	2.8	63.5	60.3						
50X50X32	2X2X1 1/4	60.5	42.7	54.9	2.8	37.1	2.8	63.5	57.2						
50X50X25	2X2X1	60.5	34.0	54.9	2.8	28.4	2.8	63.5	50.8						
65X65X50	2 1/2X2 1/2X2	76.3	60.5	70.3	3.0	54.9	2.8	76.2	69.9						
65X65X40	2 1/2X2 1/2X1 1/2	76.3	48.6	70.3	3.0	43.0	2.8	76.2	66.7						
80X80X65	3X3X2 1/2	89.1	76.3	83.1	3.0	70.3	3.0	85.7	82.6						
80X80X50	3X3X2	89.1	60.5	83.1	3.0	54.9	2.8	85.7	76.2						
80X80X40	3X3X1 1/2	89.1	48.6	83.1	3.0	43.0	2.8	85.7	73.0						

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 316LW	名称 径違いチーズ	図面番号
検図 芦田	尺度 フリー	TR(S10S)	17285
製図 滝川	日付 2017/8/08	inoc イノック株式会社	